

HIGH-TECH FOR HIGH
PRECISION MOISTURE
MEASUREMENTS.

A world first!

RELIABLE,
WIRELESS
MOBILE,
FLEXIBLE.



 **Bluetooth®**



ACCURATE - ROBUST- WIRELESS THE INNOVATIVE SOLUTION FOR MOBILE MOISTURE MEASUREMENT

Note:
Only TRIME®-TDR guarantees excellent accuracy in high saturated soils with high pore water electrical conductivity.



 **Bluetooth®**

With just one PICO-BT module you can collect the readings from a variety of sensors at different measuring locations. PICO-TALK recognises the serial number of the connected sensor and saves the reading in your system along with this information.

Choose **IMKO's robust PDA** or use any commercially available PDA with Bluetooth® and Microsoft® Windows Mobile®

PICO-BT, the Bluetooth® module for the PICO sensors, is included with the **PICO-TALK** software for Microsoft® Windows Mobile®

The **TRIME-PICO64** soil moisture sensor with an integrated soil temperature measurement system.

- Large measuring volume
- The best solution for heterogeneous and stony soils

The **TRIME-PICO32** soil moisture sensor with an integrated soil-temperature measurement system.

- Ideal for irrigation control systems and soil moisture monitoring
- Perfect for sandy and loamy soils


The **TRIME-PICO IPH** tube access probe permits rapid, reliable, and non-destructive recording of water content profiles.

- Large measuring volume
- Ideal for soils with high conductivity



PICO-TALK THE MANAGEMENT SOFTWARE FOR PICO SENSORS

Your Bluetooth module PICO-BT includes our easy-to-use PICO-TALK software for Microsoft® Windows Mobile®. To make it even easier to operate we can provide the software in 3 different languages: German, English, and Chinese. PICO-TALK's individual menus are set out clearly and can all be reached with a single touch of your fingertip.



PICO-TALK's graphical user interface is optimised for single-handed field applications

RAPID AND SIMPLE MEASUREMENTS

Simply insert your TRIME-PICO sensor into the ground and start the measurement process by pressing your PICO-TALK software's "MEAS" button. You receive an accurate moisture reading within only



2 seconds. In the case of buried sensors you also receive a reading for the soil temperature. The readings are saved directly in the system along with the time and date, enabling you to track what was measured when.

SAVE READINGS RELIABLY

You also have the option of giving a specific designation to measuring locations and saving the reading under this name.

CUSTOMISED CALIBRATION




TRIME-PICO sensors are supplied with precise soil calibration and can be used straightaway. If you prefer, you can perform the calibration process yourself and save the results in the sensor. PICO-TALK recognises the saved calibrations in the sensor and displays them in PICO-TALK for easy selection.

EFFORTLESS EXPORT OF READINGS

Do you want to use your readings in other systems? No problem. Your saved data can be exported easily in any application.

THE DIFFERENCE IS IN THE MEASUREMENT VOLUME



TRIME-PICO64 has a very large measurement volume of > 1250ml and thereby guarantees representative readings even in heterogeneous soils.

Other sensors only have a small measurement volume of < 250ml and therefore provide less conclusive results about the moisture in soil.

“The TRIME-PICO series is the most innovative solution for highly-accurate moisture measurement. We have carried out tests with the instruments usually available on the market and none of them except TRIME was able to achieve a high level of accuracy in very saline soil. And thanks to Bluetooth, interfering wires are a thing of the past in mobile applications in the field. Top marks from us for the TRIME measurement system.”
Prof. Dr. Christof Hübner, University of Applied Sciences in Mannheim

TRIME-PICO IPH FOR ACCURATE MEASUREMENTS OF WATER CONTENT PROFILES

For the first time ever, the rapid, routine and non-destructive measurements of water content profiles is possible without the use of hazardous radioactive materials.

The TRIME tube probes comprise a cylindrical PVC casing with four spring-mounted aluminium plates on opposite sides. The measurements are performed from within TECANAT plastic access tubes which can be left in the soil. The tubes must be installed prior to the taking the measurements by using a specially developed drilling set. Use up to 3m length of probe cable and tubes.



THE LATEST TECHNOLOGY FOR THE BEST MEASUREMENTS

Technical Data



TRIME®-PICO64

TRIME®-PICO32

TRIME®-PICO IPH T3/44

Power supply:	7V..24V-DC								
Power consumption:	100mA @ 12V/DC during 2..3sec. of measuring								
Moisture measuring range:	0..100% volumetric water content								
Accuracy (in % volumetric water content):									
conductivity range:	0..6dS/m	6..12dS/m	12..50dS/m	0..6dS/m	6..12dS/m	12..50dS/m	0..6dS/m	6..12dS/m	>12dS/m
Moisture range 0..40%:	±1%	±2%	with material	±1%	±2%	with material	±2%	±3%	
Moisture range 40..70%:	±2%	±3%	specific cali- bration	±2%	±3%	specific cali- bration	±3%	±4%	with tube access probe T3C/44
Repeating accuracy:	±0.2%	±0.3%		±0.2%	±0.3%		±0.3%	±0.5%	
Temperature caused drift of electronics (full range):	±0.3%								
Soil temperature measuring range:	-15°C...50°C								
Soil temperature measuring accuracy:	±0,2°C								
Measurement volume:	1,25L ± 160x100mm diameter			0,25L ± 110x50mm diameter			3,0L ± 180x150mm diameter		
Operating Temperature:	-15°C...50°C (extended temperature range on request)								
Calibration:	Calibration for a wide range of standard soil types (in accordance with Topp (equation))								
	standard calibration for most soils, customizable material specific calibration, storage of up to 15 user defined calibration curves, calibration of dielectric permittivity is possible			standard calibration for most soils, customizable material specific calibration, storage of up to 15 user defined calibration curves, calibration of dielectric permittivity is available			standard calibration for most soils, customizable material specific calibration, storage of up to 15 user defined calibration curves, calibration of dielectric permittivity is possible		
Probe body:	waterproof sealed PVC (IP68)								
Size:	155 x Ø63mm			155 x Ø32mm			166 x Ø32mm		
Rod length:	standard: 160mm			standard: 110mm			standard: 180mm		
Rod diameter:	6mm			3,5mm			-		
Interfaces:	IMP-BUS RS485 Analogue output: 2x 0..1V, 0(4)..20mA ¹ 0..100% vol. water content -40..+70°C soil temperature								
Option 1 (RS485 & analogue):	1,5m cable with 7-pin female connector								
Option 2 (IMP-BUS):	5m cable with 4-pin female connector								
Option 3 (all interfaces):	5m cable with end splices (all interfaces)								

Optional available for cable extension: E-BOX (cable extension box)
¹Optional available for cable extension and current output: C-BOX (0..1V to 0(4)..20 mA converter box)

Features PICO-BT module



Connectable Probes: PICO64, PICO32, PICO-IPH (measurement of soil profiles)
Class 2 Bluetooth® module, Bluetooth® specification 2.0 compatible
Up to 10 meter range
Internal rechargeable battery
Optimal power management
Operating Temperature: -20°C...70°C
Number of measurements with one charge: > 1500
Ni-MH (4 x 1.2V) (AA) Rechargeable Batteries, 1000mAh

Features Software PICO-TALK



Platform: Microsoft® Windows Mobile® 6.0 or 5.0 or Windows® CE
Easy to install and use
Stores many thousand measurements
Up to 15 user defined calibrations selectable
Intuitive user interface
Touch screen operation
3 different languages: German, English and Chinese
Requires less memory

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by IMKO GmbH is under license. Other trademarks and trade names are those of their respective owners.

Microsoft®, Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

All indicated data serve alone the product description and are not as characteristics in the legal sense to be understood. Subject to alterations.